



**Equipment
Catalog for Rental**



ECG ELI 230

Interpretation

Backlit, 1/4 VGA 320 x 240 LCD color display
12-lead electrocardiograph
Simultaneous acquisition of all 12 leads
40,000 s/sec/channel used for pacemaker spike detection

1000
s/
sec/

channel used for recording and analysis
Pacemaker spike markers, for both atrial and



Elitech RC-4

This data logger is mainly used for temperature recording during storage and transportation of foodstuff, medicine, chemicals and other products, especially widely used in all links of warehousing, logistics and cold chain, such as refrigerated containers, refrigerated trucks, refrigerated package, cold storage, laboratory, etc. Temperature measuring range: $-30^{\circ}\text{C} \sim +60^{\circ}\text{C}$; for optional external sensor, $-40^{\circ}\text{C} \sim +85^{\circ}\text{C}$;



Elera M230

LED display
Low battery indicator
Automatic shutdown.
Features:
Color: Black
Power supply: 2 * AAA 1.5V
Auto Power Off: Auto power off in the absence of a signal for more than 8 seconds
Size: 5.7 × 3.1 × 3 cm
Weight: 54 g



Heaco CMS50C

The device has a 1.1-inch color screen. SpO2 data are measured in the range of 0-100%, and heart rate is 30-250 beats / min. In addition to the numerical values, the pulse oximeter displays a pulse wave and can display parameters in four directions. The CMS50C is controlled by just one button and automatically shuts down if measurement does not take more than 5 seconds.



Vestfrost VTS098

Premium Ultra Low Temperature -86° Freezer

The brand new VTS 098 -86°C undercounter offers a unique combination space-saving design, large 93L storage capacity and advanced technology



Vestfrost VT208

Ultra Low Temperature Freezer -86°C

The VT low temperature freezers create the possibility to maintain temperatures as low as -86°C. Supreme stability, reliability, user-friendliness and ease of cleaning make these freezers an ideal solution for laboratories and hospitals. Nature R refrigerant, cyclopentane insulation combined with recyclable materials make the





J4

Display: 720x1280 px

Processor: 1.4GHz quad-core

RAM: 2GB

BATTERY: 3000mAh



J3

Display: 720*1280px

Processor : 1.5GHz quad-core

RAM: 1.5GB.

Battery Capacity: 2600mAh.

Infusomat® compact+

B. Braun compact^{plus} is the new generation of infusion pump, offering a large colour display, guided loading, novel intuitive user interface, integrated DoseGuard™ drug library, and Li-Ion battery. The compact^{plus} integrates the latest technological advances whilst maintaining simplicity and reliability through maintaining the proven robustness of the original compact pump range.



Heaco SN-1800

Infusion pump Heaco SN-1800 - is a device for continuous dosed injection of the drug solution. Ciliates uses the vertical load on the system and supports the infusion line from all manufacturers. It is recommended for surgery departments, paediatrics and intensive care units.





Biological Safety Cabinet

BSC-A2-X Series Class II A2 Biological Safety Cabinet Class II Type A2

Advantage:

1. Motorized front window.
2. Time reserve function.
3. ULPA filter life and UV life indicator.
4. Automatic air speed adjustable with filter block.
5. With memory function in case of power-failure.
6. Audio and visual alarm
7. Work area surrounded by negative pressure
8. Audio and visual alarm



DISCLAIMER

- Timeline on 48 hours delivery starts after signature proposal, or purchase order or signed contract.
- The delivery within 48 hours applies only to the products listed in this catalogue. Delivery timelines for other products may vary and should be requested from IRM.
- The delivery is done within the territory of Ukraine (except for temporary occupied territories).



CONTACTS

+38 063 561 7041

info@irm-europe.com

21050, Ukraine, Vinnytsya,

37 Teatralna str., office 3.